



### SAFE 4 XC

Safer 4 XC solvent resistant films provide highly effective protection against tags and graffiti. The film's protective qualities are not limited to solvents, it will also shield a window's surface from other acts of vandalism involving scratching or acid etching. An easy film to install and replace, it is also classed as a security film, providing protection by holding shattered glass in place in the event of an explosion or serious impact.



SOLAR SCREEN® Warranty  
See the notice "new guarantees for the external films"



Fire-resistance rating  
**M1**



Storage from -5°C to +40°C  
**3 YEARS**



REACH RoHS compliant  
**RESPECTED**

### WIDTHS AVAILABLE:

- ↔ **122 cm**
- ↔ **152 cm**
- ↔ **183 cm**

### TECHNICAL DATASHEET


Data calculated based on film applied to clear glass 3 mm thick (\*on double glazing 4-16-4)

Ultraviolet transmission	5 %
Visible light transmission	85 %
Reflection of external visible light	11 %
Reflection of internal visible light	11 %
Total solar energy rejected	19 %
Total solar energy rejected 2*	19 %
Solar ratio :	
Solar energy reflection	9 %
Solar energy absorption	14 %
Solar energy transmission	77 %
Reduction in Solar Glare	14 %
g-value	0.83
u-value	5.7
Shading coefficient	0.9
Installation type : External application	
Roll length	30,5 m
PET / PVC composition	PET
Thickness	120 µ

Colour : TRANSPARENT

### CONSTRUCTION

1. "Hard" scratch resistant layer, for durability and ease of maintenance during window cleaning
2. High optical quality polyester
3. Bonding adhesive
4. High optical quality polyester
5. Reinforced PS Adhesive to accompany the elasticity of the film in case of impact, glass polymerization within 30 days
6. Protection release liner, disposable after installation



### INSTALLATION ADVICE

Vertical installation and on standard glass surface\*\*

Clear single pane	✓
Tinted single pane	✓
Reflective tinted single pane	✓
Clear double pane	✓
Tinted double pane	✓
Reflective tinted double pane	✓
Gas-filled double pane - Low E	✓
STADIP EXT. clear double pane	✓
STADIP INT. clear double pane	✓

✓ Yes ! Caution ✗ Not recommended

\*Recommendations provided on the basis of a glazed surface covering up to 2.5m<sup>2</sup>.

### MAINTENANCE INSTRUCTIONS

Soapy water solution (ref. 0805 Film on), do not clean for at least a month and do not apply any type of sticker or adhesive on the film.

*Non-contractual data, SOLAR SCREEN® reserves the right to modify the composition of its films at any time. Consult our guarantee vouchers and our general conditions of sale.*