



### CLEAR 8 XC

Clear 8 XC films help secure your windows by ensuring that the glass does not shatter, remaining transparent and retaining its overall integrity in the event of an impact, explosion or fire. Comply with European Standard EN 12600.



SOLAR SCREEN® Warranty  
See the notice "new guarantees for the external films"



Fire-resistance rating  
**M1**



Storage from -5°C to +40°C  
**3 YEARS**



European Standard EN 12600  
**1B1**



REACH RoHS compliant  
**RESPECTED**

### WIDTHS AVAILABLE:

↔ **152 cm**

↔ **183 cm**

### TECHNICAL DATASHEET


Data calculated based on film applied to clear glass 3 mm thick (\*on double glazing 4-16-4)

Ultraviolet transmission	1 %
Visible light transmission	83 %
Reflection of external visible light	10 %
Reflection of internal visible light	10 %
Total solar energy rejected	20 %
Total solar energy rejected 2*	21 %
Solar ratio :	
Solar energy reflection	10 %
Solar energy absorption	14 %
Solar energy transmission	76 %
Reduction in Solar Glare	15 %
g-value	0.82
u-value	5.7
Shading coefficient	0.9
Installation type : External application	
Roll length	30,5 m
PET / PVC composition	PET
Thickness	240 µ

Colour : TRANSPARENT

### CONSTRUCTION

- "Hard" scratch resistant layer, for durability and ease of maintenance during window cleaning
- High optical quality polyester
- Bonding adhesive
- High optical quality polyester
- Reinforced PS Adhesive to accompany the elasticity of the film in case of impact, glass polymerization within 30 days
- Protection release liner, disposable after installation



### INSTALLATION ADVICE

Vertical installation and on standard glass surface\*\*

Clear single pane	✓
Tinted single pane	✓
Reflective tinted single pane	✓
Clear double pane	✓
Tinted double pane	✓
Reflective tinted double pane	✓
Gas-filled double pane - Low E	✓
STADIP EXT. clear double pane	✓
STADIP INT. clear double pane	✓

✓ Yes    ⚠ Caution    ✗ Not recommended

\*\*Recommendations provided on the basis of a glazed surface covering up to 2.5m<sup>2</sup>.

### MAINTENANCE INSTRUCTIONS

Soapy water solution (ref. 0805 Film on), do not clean for at least a month and do not apply any type of sticker or adhesive on the film.

*Non-contractual data, SOLAR SCREEN® reserves the right to modify the composition of its films at any time. Consult our guarantee vouchers and our general conditions of sale.*